IB1 Load Cell

SCALE-TEC
MEASUREMENT WITH CONFIDENCE



Short description

- Nickel Plated Alloy steel IP67 shear beam load cell (100 kg, 250kg are bending beam load cells)
- Adhesive sealed
- Suitable platform weighing, bed weighing, etc.
- High accuracy
- High reliability
- Current calibrated (sc-option)

Available models

Capacity	Accuracy	Full article description
100kg	C3	IB1-C3-100kg-4M
250kg	C3	IB1-C3-250kg-4M
500kg	C3	IB1-C3-500kg-4M
1t	C3	IB1-C3-1.0t-4M
1.5t	C3	IB1-C3-1.5t-4M
2t	C3	IB1-C3-2.0t-4M
2.5t	C3	IB1-C3-2.5t-6M
3t	C3	IB1-C3-3.0t-4M
5t	C3	IB1-C3-5.0t-6M
10t	C3	IB1-C3-10t-6M

Specifications and dimensions are subject to change without notice and do not constitute any liability whatsoever.

SCALETEC MECHATRONICS PVT. LTD.
665, GIDC Industrial Estate, Makarpura,
Vadodara – 390010, Gujarat, India

T: +91 9909966404
F: +91-265-23118 4 2
info@scale-tec .i n

IB1 Load Cell

SCALE-TEC
MEASUREMENT WITH CONFIDENCE


Detailed specifications IB1

Accuracy class		C3
Output sensitivity (= FS)	mV/V	3.0 ± 0.003
Maximum capacity (E^{max})	t	0.1, 0.25, 0.3,0.5, 1,1 .5, 2, 2.5, 3, 5, 10
Max.number of load cell intervals	n_{LC}	3000
Ratio of min. LC verification interval	$Y = E_{max}/v$ min	10000
Combined Error	%FS	≤± 0.023
Minimum dead load	OfE_{max}	0%
Safe overload	of E_{max}	150%
Ultimate overload	of E_{max}	300%
Zero balance	ofFS	< ± 1.0%
Excitation, recommended voltage	V	5 ~12
Excitation maximum	V	18
Input resistance	Ω	350 ± 3.5
Output resistance	Ω	350 ± 3.5
Insulation resistance	MΩ	≥5000 (at 50VDC)
Compensated temperature	°C	-10 ~+40
Operating temperature	°C	-35 ~ +65
Storage temperature	°C	-40 ~ +80
Element material		Nickel Platted Alloy steel
Ingress Protection (acc. to EN 60529)		IP67
Recommended torque on fixation	Nm	M12:75

Wiring

Wiring:
Shielded, 4 or 6 conductor cable
Cable diameter: Ø5mm.
Standard cable length for 100kg – 2t: 4m and 6m for the higher capacities.
Shield in not connected to the element.

4-wire diagram



Specifications and dimensions are subject to change without notice and do not constitute any liability whatsoever.

SCALETEC MECHATRONICS PVT. LTD.
665, GIDC Industrial Estate, Makarpura,
Vadodara – 390010, Gujarat, India

T +91 9909966404
F +91-265-23118
info@scale-tec .in

IB1 Load Cell

SCALE-TEC
MEASUREMENT WITH CONFIDENCE


Ordering Info:

IB1 – C3 – 1.0t – 4 – – MX – SC – XX


- XX: Option XX. No mark is standard version, W4 is through loading hole, W6 is "T" end loading hole.
- SC: Option SC (standard current).
- MX: Cable option. No mark is 4 conductor cable and with a "6" a 6 conductor cable.
- (blank): Thread option. No mark is Metric Thread and "Y" is Imperial thread.
- 4: Length of the cable in meters.
- 1.0t: Nominal capacity (*Emax*) for Metric in t(on) and Imperial in lbs up to 500lbs and above in K(ilo)lbs.
- C3: Maximum load cell divisions.
- IB1: Load Cell model.

Dimensions in mm

Standard version



Option W4 version (Through loading hole)




Specifications and dimensions are subject to change without notice and do not con stitute any liability whatsoever.

SCALETEC MECHATRONICS PVT. LTD.
665, GIDC Industrial Estate, Makarpura,
Vadodara – 390010, Gujarat, India

T: +91 9909966404
F: +91-265-23118 4
2 info@scale-tec .in

Option W6 version (“T” end loading hole)







Dimension Capacity	L	L1	L2	L3	L4	B	B1	H	H1	H2	H3	H4	ØD	Ø D 1	Ø d 1	Ø d 2	M
0.1t-2t	130	15.8	25.4	76.2	54.2	31.8	34	31.8	15.8	14.5	15.8	4.8	13.5	18	4	2	M 12
2.5t-5t	171.5	19.1	38.1	95.3	77.2	38.1	40	38.1	18.8	17.5	18.8	4.8	19.8	25	4	2	M 18
10t	222.3	25.4	50.8	120.7	101.6	50.8	52.4	50.8	25.4	-	-	-	26	-	-	-	M 24

Specifications and dimensions are subject to change without notice and do not constitute any liability whatsoever.

SCALETEC MECHATRONICS PVT. LTD.
665, GIDC Industrial Estate, Makarpura,
Vadodara – 390010, Gujarat, India

T: +91 9909966404
F: +91-265-23118 4 2
info@scale-tec .i n

Available accessories

HJ-8-201-0.1-10t foot • Ø60-86 and height 92-112 mm • Nickel plated alloy steel • Adjustable height	
HJ-8-203-0.5-2t foot • Ø67 andheight 46 mm • Nickel plated alloy steel • Easy installation	
HJ-8-213-0.5-2t foot • Ø60andheight 62 mm • Nickel plated alloy steel • Adjustable height	
HM-8-402-0.5-5 moun Nickeplate allo stee Adjustabl mountin heigh Eas installatio	
HY-8-102-0.5-5 Nicke plate allo stee Eas installatio Goo self-alignmen abilit	
HD-8-301-0.5-5 space plat Nickeplate allo Stee	

Specifications and dimensions are subject to change without notice and do not constitute any liability whatsoever.

SCALETEC MECHATRONICS PVT. LTD.
665, GIDC Industrial Estate, Makarpura,
Vadodara – 390010, Gujarat, India

T +91 9909966404
F +91-265-23118
info@scale-tec.ini

IB1 Load Cell

SCALE-TEC
MEASUREMENT WITH CONFIDENCE


Ordering Info:

IB1 – C3 – 1.0t – 4 – – MX – SC – XX


- Option XX. No mark is standard version, W4 is through loading hole, W6 is "T" end loading hole.
- Option SC (standard current).
- Cable option. No mark is 4 conductor cable and with a "6" a 6 conductor cable.
- Thread option. No mark is Metric Thread and "Y" is Imperial thread.
- Length of the cable in meters.
- Nominal capacity (*Emax*) for Metric in t(on) and Imperial in lbs up to 500lbs and above in K(ilo)lbs.
- Maximum load cell divisions.
- Load Cell model.

Dimensions in mm

Standard version



Option W4 version (Through loading hole)



Specifications and dimensions are subject to change without notice and do not con stitute any liability whatsoever.

SCALETEC MECHATRONICS PVT. LTD.
665, GIDC Industrial Estate, Makarpura,
Vadodara – 390010, Gujarat, India

T: +91 9909966404
F: +91-265-23118 4
2 info@scale-tec .in